

Fixed–mobile Convergence: Structural convergence

Preliminary results

<i>Dirk Breuer</i>	<i>Deutsche Telekom Laboratories, Germany</i>
<i>Tibor Cinkler</i>	<i>Budapest University of Technology and Economics, Hungary</i>
<i>Stéphane Gosselin</i>	<i>Orange R&D, France</i>
<i>Annie Gravey</i>	<i>Telecom Bretagne, France</i>
<i>Ali Hamidian</i>	<i>Ericsson Research, Sweden</i>
<i>Stefan Höst</i>	<i>Lund University, Sweden</i>
<i>Tahar Mamouni</i>	<i>Orange R&D, France</i>
<i>Péter Olaszi</i>	<i>AITIA International, Inc., Hungary</i>
<i>Stephan Pachnicke</i>	<i>ADVA Optical Networking SE, Germany</i>
<i>Björn Skubic</i>	<i>Ericsson Research, Sweden</i>
<i>Jose Torrijos Gijón</i>	<i>Telefónica Investigación y Desarrollo, Spain</i>
<i>Erik Weis, Frank Geilhardt, Thomas Monath, Sandro Krauß</i>	<i>Deutsche Telekom Laboratories, Germany</i>

This ongoing work receives funding from the European Union's Seventh Framework Programme (FP7/2007-2013) under grant agreement n° 317762 "COMBO project"

Technology comparison: Backhaul

Example: Main CO Urban FTTH area

Backhaul, urban		Reference	NG-PON2	WR-WDM-PON	WS-WDM-PON
System elements per service area	Σ OLT shelves	n/a	3	3	4
	Σ Interfaces (3 Gb/s)	1076	1122	1122	1122
	Σ Passive optics	68	172	89	118
	Σ Amplifiers	0	1	0	9
	Total Latency [μ s]	~10	~10	~10	~10
Fibres per service area	Total count (length)	825 (743 km)	661 (562 km)	789 (692 km)	800 (696 km)

- WDM overlay NG-PON2 requires more shelf space and additional amplifiers due to high power split for residential customers
- CWDM, WR and WS WDM additional infrastructure required

Technology comparison: Fronthaul

Example: Main CO Urban FTTH area

Fronthaul, urban		Reference	NG-PON2	WR-WDM-PON	WS-WDM-PON
System elements per service area	Σ OLT shelves	n/a	6	3	6
	Σ Interfaces (3 Gb/s & 10 Gb/s)	1490	2180	2180	2180
	Σ Passive optics	112	206	115	121
	Σ Amplifiers	0	20	0	12
	Total Latency [μ s]	~0.01	~0.02	~0.02	~0.02
Fibres per service area	Total count (length)	847 (785 km)	666 (572 km)	800 (696 km)	802 (700 km)

- WDM overlay NG-PON2 requires more shelf space and additional amplifiers due to high power split for residential customers
- CWDM, WR and WS WDM additional infrastructure required

Observation: Can't put the BBU hostel further from the Main CO

Summary – Preliminary qualitative assessment of coordination architectures for Backhaul and Fronthaul

Per service area (urban)	Reference	NG-PON2	WR-WDM-PON	WS-WDM-PON
Reduction in fibre count and length	•	•••	••	••
Reduction in number of interfaces	•••	••	••	••
Reduction in passive optics	•••	•	•••	••
Reduction in amplifiers (reach)	•••	•	••	•
Potential of structural convergence		•••	•	•
Number of wavelengths per fibre	•	•	•••	••
Bitrate per wavelength	••	••	••	••
Low latency (system level)	••	••	••	••
Simple to operate (colourless)		•••	•••	•••
Reduction in active shelves in Main CO	•••		•	
Ethernet aggregation in Main CO		•	•	•
Legacy compatibility with fixed net.		•••		
Re-use network infrastructure	••	•••	•	••

If low transport delay is realized backhaul + CoMP could deliver almost equal performance compared to fronthaul over existing backhaul infrastructure

Presented by

Annie Gravey annie.gravey@telecom-bretagne.eu
Péter Olaszi peter.olaszi@aitia.ai
Björn Skubic bjorn.skubic@ericsson.com

Dirk Breuer Deutsche Telekom Laboratories, Germany
Tibor Cinkler Budapest University of Technology and Economics, Hungary
Stéphane Gosselin Orange R&D, France
Annie Gravey Telecom Bretagne, France
Ali Hamidian Ericsson Research, Sweden
Stefan Höst Lund University, Sweden
Tahar Mamouni Orange R&D, France
Péter Olaszi AITIA International, Inc., Hungary
Stephan Pachnicke ADVA Optical Networking SE, Germany
Björn Skubic Ericsson Research, Sweden
Jose Torrijos Gijón Telefónica Investigación y Desarrollo, Spain

This ongoing work receives funding from the European Union's Seventh Framework Programme (FP7/2007-2013) under grant agreement n° 317762 "COMBO project"